



US005936451A

[11] Patent Number: 5,936,451

[45] Date of Patent: *Aug. 10, 1999

4,875,020	10/1989	Daniele et al.	330/307
5,006,738	4/1991	Usuki et al.	327/285
5,057,722	10/1991	Kobatake	327/288
5,068,628	11/1991	Groshal	327/7
5,081,380	1/1992	Chen	327/281
5,175,452	12/1992	Lupi et al.	327/277
5,227,679	7/1993	Woo	327/269
5,231,319	7/1993	Crafts et al.	327/277
5,300,837	4/1994	Fischer	327/281
5,317,219	5/1994	Lupi et al.	307/603
5,382,840	1/1995	Massoner	327/206

FOREIGN PATENT DOCUMENTS

0405319A1	1/1991	European Pat. Off.	H03H 11/26
0535359	8/1992	European Pat. Off.	327/288
1161913	6/1989	Japan	327/211
4-144309	5/1992	Japan	327/281

Primary Examiner—Toan Tran*Assistant Examiner*—Eunja Shin*Attorney, Agent, or Firm*—Theodore E. Galanthay; Lisa K. Jorgenson; Renee M. Larson

[57] ABSTRACT

A reduced area delay circuit and method are disclosed. The delay circuit uses a constant current source and a constant current drain to charge and discharge a capacitor and thus control the delay time of the delay circuit. The constant current source and drain can be implemented using current mirrors formed by configuring MOSFET transistors in a common source configuration. The delay circuit method includes the steps of receiving an input signal, delaying the input signal by using a constant current source or drain in combination with a capacitor, and then buffering the voltage on the capacitor using two inverters. A programmable delay circuit is also disclosed by adding additional pairs of current mirrors to the delay circuit and selectively enabling the pairs to adjust the delay time.

15 Claims, 2 Drawing Sheets

FOOTNOTES